ProSoft® Extra Coarse Solar Salt



Product Name: ProSoft Extra Coarse Solar Salt

Source: Ogden, Utah, U.S.

Production Locations: Ogden, Utah, U.S.; Milwaukee, WI, U.S.

Packaging: Bags

Application: Water softening salt for water conditioning

Chemical Analysis							
Constituent	Formula	Unit	Min / Max				
Sodium Chloride	NaCl	(%)	98.5 MIN				
Calcium Sulfate	CaSO4	(%)	1.5 MAX				
Magnesium chloride	MgCl2	(%)	0.5 MAX				
Moisture	H2O	(%)	0.05 MAX				
Water Insolubles		(%)	0.15 MAX				

Particle Size Distribution, Cumulative % Retained							
Tyler Mesh	US Mesh	Opening (in)	Typical Range				
	3/8"	0.375	0-3				
4	4	0.187	15 -25				
8	8	0.0937	75-95				
30	30	0.0234	80-100				
Pan	Pan		100				



Physical Properties				
Measurement	Typical			
Bulk Density	63 lb/ft ³			

Packaging					Palletization				
UPC Code	Product Code	Description	Size (lb)	Volume (ft³)	Dimensions (W" x L" x H")	Bags per Pallet	Dimensions (w" x L" x H")	Weight (Ib)	Pallet Pattern (Ti x Hi)
004148234 5500	767148	Poly Bag	50	0.75	25 x 13 x 4	49	48 x 40 x 36	2515	7 x 7

• Certified by the National Sanitation Foundation (NSF) to NSF/ANSI/CAN 60

Compass Minerals | 877-462-7258

9900 West 109th Street, Suite 100, Overland Park 66210

This information is based on our present state of knowledge and is intended to provide general notes on the product(s) supplied by us and their uses. The information should not be construed as a specific property promise or guarantee of the product(s). Chemical Analysis and Screen Data are based on the previous year's historical data.