

Product Data Sheet

Product Description

- Sodium chloride is compacted into pellets, admixed, and quality control tested
- Conforms to the American Water Works Association Standard B200-17
- Certified by NSF to NSF/ANSI/CAN Standard 60

Admixture

- Resin Clean® is a proprietary additive for water softener resin maintenance

Production Location

- Duluth, Minnesota – USA



Physical Properties

- Bulk Density: 61 lb/ft³
- Approximate Pellet Dimensions:
 - Length: 1.125"
 - Width: 0.625"
 - Depth: 0.375"

Chemical Analysis				
Constituent		Units	Typical	Range
Sodium Chloride	NaCl	(%)	99.82	99.34 - 100.0
Calcium	Ca	ppm	194	0 - 541
Magnesium	Mg	ppm	179	0 - 545
Potassium	K	ppm	425	0 - 1114
Sulfate	SO ₄	ppm	911	0 - 5458
Water Insolubles		ppm	74	0 - 295

Typical Screen Data				
U.S.S. Mesh	Tyler Mesh	Open (in)	Typical Retained %	Range %
4	4	0.187	96.0	92 - 100
Pan	Pan		4.0	0 - 8

Method of Analysis - American Society for Testing and Materials Procedure E534.
All other testing is from Compass Minerals' internal quality control procedures.

Packaging							Palletization			
UPC Code	New Product Code	Old Product Code	Description	Size (lb)	Volume (ft ³)	Dimensions (W" x L" x H")	Bags per Pallet	Dimensions (W" x L" x H")	Weight (lb)	Pallet Pattern (Ti x Hi)
041482-311406	765388	31140	Bag	40	0.61	27 x 13 x 3	63	48 x 40 x 35	2585	7 x 9
041482-311505	765476	31150	Bag	50	0.75	25 x 13 x 4	49	48 x 40 x 36	2515	7 x 7

Compass Minerals
9900 West 109th Street – Suite 100
Overland Park, Kansas 66210
Ph: 800-755-7258 Fax: 800-359-7258

This information is based on our present state of knowledge and is intended to provide general notes on the product(s) supplied by us and their uses. The information should not be construed as a specific property promise or guarantee of the product(s). Chemical Analysis and Screen Data are based on the previous year's historical data.